

Switch-Disconnectors, Load Switches & Control Stations







Encl. Ref.	Encl. Dim.				Encl. Dim.			Cable Entries.	Line Drg.
	H	W	D	D1	H1	W1	d		
GRP Enclosures									
GP1	303	265	167	-	222	184	-		Fig. 4
GP3	428	325	183	-	348	245	-		Fig. 4
GP6	500	430	210	-	423	353	-		Fig. 4
Insulated Enclosures									
KSA	120	85	80	-	110	-	4.2	4 x 20mm k'outs	Fig. 1
KSAV/KS51V	120	85	90	-	110	-	4.2	4 x 20mm k'outs	Fig. 1
KLBV/KL51V	160	85	82	-	150	-	4.2	4 x 20mm k'outs	Fig. 1
KLC	190	100	91	-	178	-	5.6	4 x 25mm k'outs	Fig. 1
KLCV/KL11V	190	100	93	-	178	-	5.6	4 x 25mm k'outs	Fig. 1
KLD	250	145	107	-	229	124	6.5	4 x 25mm k'outs	Fig. 2
KLDV/KL71V	250	145	107	-	229	124	6.5	4 x 40mm k'outs	Fig. 2
KLE	250	145	107	-	229	124	6.5	4 x 40mm k'outs	Fig. 2
P1Y	80	72	56	-	66.5	58.5	4.5	1 x 20mm + 2 x 20/25mm k'outs	Fig. 3
P2Y	85	85	101	-	40	65	5.5	3 x 20mm k'outs	Fig. 9
PF1A	72	64	42	-	36	50	4.4	4 x 20mm ISO	Fig. 2
PF1B	72	64	51	-	36	50	4.4	4 x 20mm ISO	Fig. 2
PF1E	92	82	65	-	52	68	4.4	4 x 20mm ISO	Fig. 2
PF1F	92	82	90	-	52	68	4.4	4 x 20mm ISO	Fig. 2
PN1C	72	64	56	-	36	50	4.4	4 x 20mm ISO	Fig. 2
PN1G	72	64	69	-	36	50	4.4	4 x 20mm ISO	Fig. 2
ST1B	180	140	115	-	150	128	5	4 x 20mm ISO	Fig. 2
ST2	280	190	130	-	254	164	7	2 x gland plates	Fig. 2
ST3	380	280	180	-	354	254	7	2 x gland plates	Fig. 2
ST4/STM	560	380	180	-	534	354	7	2 x gland plates	Fig. 2
STA	190	190	180	-	164	164	7	-	Fig. 2
STB	280	190	130	-	254	164	7	1 x gland plate	Fig. 2

Painted & Stainless Steel Enclosures



MB1	164	94	80	8	103	112	6	-	Fig. 4
MB2	194	119	115	8	133	137	6	-	Fig. 4
MB3/MB3E	254	149	125	8	193	167	6	-	Fig. 4
MB4	190	234	150	8	248	252	6	-	Fig. 4
MB8/SB8	400	300	175	-	340	240	6.5	2 x gland plates	Fig. 6
MB9/SB9	500	400	175	-	440	340	6.5	2 x gland plates	Fig. 6
MB10	500	400	300	-	440	340	6.5	2 x gland plates	Fig. 6
MB25/SB25	650	450	225	-	590	390	6.5	2 x gland plates	Fig. 6
MB26/SB26	800	550	225	-	740	490	6.5	2 x gland plates	Fig. 6
MB27/SB27	900	600	300	-	840	540	6.5	2 x gland plates	Fig. 6
MB28/SB28	1000	800	400	-	940	740	6.5	4 x gland plates	Fig. 6
MB20	250	175	175	-	225	195	6	-	Fig. 4
MB22	400	300	275	-	340	240	6.5	2 x gland plates	Fig. 6
SB1	164	94	81.5	-	103	112	6	-	Fig. 5
SB2	194	119	116.5	-	133	137	6	-	Fig. 5
SB3/SB3E	254	149	126.5	-	193	167	6	-	Fig. 5
SB4	309	234	151.5	-	248	252	6	-	Fig. 5
SB30	100	100	91.5	-	120	70	6.5	-	Fig. 7

Flush mounting - Stainless Steel

Encl. Ref.	Front Plate			Adaptable Box			Cable Entries.	Line Drg.
	H	W	D	H1	W1	D		
SF1	100	100	2	78	78	77	8 x 20mm k'outs	Fig. 8
SF1A	100	100	2	78	78	52	8 x 20mm k'outs	Fig. 8
SF2	125	125	2	103	103	77	12 x 20mm k'outs	Fig. 8
SF3	175	175	2	153	153	102	16 x 20mm k'outs	Fig. 8



* EXTERNAL MTG. BKT'S - IF FITTED THEY ADD 120mm TO EITHER W1 OR H1 DIMENSION & d Ø = 8.5 DIA.



ADAPTABLE BOX

